

Two solid imagers in one – for  
unprecedented versatility.

# VIPER

si2™ SLA® SYSTEM

3D Systems' new Viper si2 SLA system is our first solid imaging system to combine standard AND high-resolution part building in the same system. Now, with one machine, you can tackle an unequalled range of solid imaging applications. And you can take advantage of scores of cost-saving, productivity-enhancing innovations, including state-of-the-art components, improved system software, and much more.

**A DUAL-RESOLUTION AND LONGER LIFE LASER -- ANOTHER 3D SYSTEMS FIRST.** The Viper si2 system lets you choose between standard resolution mode, for the best balance of build speed and part resolution, and high resolution (HR) mode for ultra-detailed small parts and features -- all from a carefully integrated digital signal processor (DSP) controlled high speed scanning system with a single, solid-state laser that delivers 100 mW of available power.

**BUILD SUPERIOR QUALITY PARTS FOR EVERY APPLICATION.** The Viper si2 system builds parts with a smooth surface finish, excellent optical clarity, high accuracy, and thin, straight vertical walls. It's ideal for a myriad of solid imaging applications, from rapid modeling and prototyping, to injection molding and investment casting.



**LOWER YOUR COST OF OWNERSHIP THANKS TO SCORES OF DESIGN IMPROVEMENTS.** Longer laser life is just the beginning. Optimized for the proven CibaTool® SL materials, the system's new solid-state Viper laser delivers fast draw speeds, and high throughput. What's more, the entire system – from optics and electronics to the external enclosure – has been designed from the ground up for maximum productivity, reliability and serviceability.

**UPGRADED SOFTWARE, UPGRADED CAPABILITIES.** The Viper si2 system comes fully equipped with upgraded versions of 3D Lightyear™ part preparation and Buildstation™ control software, with Buildstation software continuing to provide unparalleled control over the build process.



## Tackle all these applications with one machine:

- SMALL TO MEDIUM-SIZED CONCEPT AND COMMUNICATION MODELS
- SMALL TO MEDIUM-SIZED PROTOTYPES
- PATTERNS FOR INJECTION MOLDING
- PATTERNS FOR INVESTMENT CASTING
- PRECISION BUILDS OF EXTREMELY DETAILED PARTS
- PARTS WITH EXTREMELY FINE DETAIL

### *Strategic Benefits*

- Longer laser life
- Lower cost of ownership
- Faster scanning system
- Consistent part quality
- Greater range of applications

**si<sup>2</sup>**  
SLA® SYSTEM

# Viper si2 SLA System Specifications

Standards and Regulations: This SLA system conforms to Federal Laser Product Performance Standards 21CFR1040.10 Class I laser in normal operation. During field service, emission levels can correspond to Class IV laser product. The Viper si2 system complies with CE requirements.

LASER	
Type	Solid state Nd:YVO <sub>4</sub>
Wavelength (epoxy resins)	354.7 nm
Power at vat	100 mW available
Laser Warranty	7,500 hours or 12 months (whichever comes first)
RECOATING SYSTEM	
Process	Zephyr™ recoating system
Minimum build layer	0.05 mm (0.002 in) *
Tested build style for SL 7540 material:	0.10 mm (0.004 in) - EXACT™ build style *
Tested build styles for SL 5510 material:	0.10 mm (0.004 in) - EXACT build style *
	0.15 mm (0.006 in) - QuickCast™ build style *
	0.05 mm (0.002 in) - HR EXACT build style *
OPTICAL & SCANNING	
Beam (diameter @ 1/e <sup>2</sup> )	Standard mode 0.250 +/- 0.025 mm (0.010 +/- 0.001 in) Hi res mode 0.075 +/- 0.015 mm (0.0030 +/- 0.0005 in)
ELEVATOR	
Vertical resolution	0.0025 mm (0.0001 in)
Position repeatability	0.0076 mm (0.0003 in)
Maximum part weight	9.1 kg (20 lb)
Typical velocity during part building	5 mm/sec (0.2 in/sec)
VAT CAPACITY	
Volume	32.21 L (8.5 U.S. gal)
Maximum build envelope in standard mode	250 x 250 x 250 mm XYZ (10 x 10 x 10 in)
Maximum build envelope in HR mode	125 x 125 x 250 mm XYZ (5 x 5 x 10 in)
Interchangeable vat	Yes
SYSTEM CONTROLLER & SOFTWARE	
Control software	Buildstation 5.2 software
Operating system	Windows NT (4.0)
Input data file format	.stl .slc
Available fixed disk capacity	20 GB
Network type and protocol	Ethernet, IEEE 802.3 10/100 Base-T
POWER	
100 - 120 VAC +/-10% 50/60 Hz, 6 amps	15 amp, 115V
220 - 240 VAC +/-10% 50/60 Hz, 3 amps	8 amp, 230V
UPS power rating	2KVA minimum
AMBIENT TEMPERATURE	
Temperature range	23°C +/- 3°C (73°F +/- 5°F)
Maximum change rate	1°C/hour (3.4°F/hour)
Relative humidity	20 - 50%, non condensing
SIZE	
Crated machine	W168 x D102 x H211 cm (W66 x D40 x H83 in)
Uncrated machine	W134 x D86 x H178 cm (W52.5 x D33.5 x H70 in)
WEIGHT	
Crated machine	564 kg (1,242 lb)
Uncrated machine	463 kg (1,020 lb)
OPTIONS	
Additional interchangeable vats	
Additional build platforms	
Post Curing Apparatus (PCA™) equipment	
SYSTEM WARRANTY	
One year from installation date.	
Includes parts, labor, and 3D Systems' software upgrades.	

\* Dependent upon part geometry, build parameters and material.



## 3D Systems

26081 Avenue Hall

Valencia, CA 91355 USA

telephone 661.295.5600, ext. 2882

fax 661.294.8406

toll free 888.337.9786

email [moreinfo@3dsystems.com](mailto:moreinfo@3dsystems.com)

[www.3dsystems.com](http://www.3dsystems.com)

Nasdaq: TDSC

### FRANCE

telephone +33 1 69 35 17 17

### GERMANY

telephone +49 6151 357 303

### HONG KONG

telephone +852 2923 5077

### ITALY

telephone +39 039 68 904 00

### JAPAN

telephone +03 5288 5951

### SPAIN

telephone +34 93 751 49 49

### UK

telephone +44 1442 282600

© Copyright 2001 by 3D Systems. All rights reserved. Specifications subject to change without notice. The 3D logo and SLA are registered trademarks and 3D Systems, si2, Lightyear, EXACT, Buildstation, PCA, QuickCast, and Zephyr are trademarks of 3D Systems. CIBATool is a registered trademark of Vantico Inc. All other product names or services mentioned are trademarks or registered trademarks of their respective companies.

P/N 70433 8/01